

Andover Washed block paving product information



Premium washed block for prestigious schemes.

- Pale, understated colour creates a contemporary backdrop to either modern or traditional projects
- Can be used to create different patterning effects in adjacent areas while retaining overall texture and colour consistency
- Guaranteed minimum 50% recycled material in the back mix
- Available as an Infiltra concrete block permeable paver (CBPP)
- Chamferless profile creates a smoother riding surface
- Available in long aspect paving for a versatile contemporary look
- Semi dry manufacturing process then washed
- Andover steps also available within the range

Applications

Andover washed block paving is suitable for prestigious pedestrian areas and building developments including town centres and shopping precincts. Refer to our technical department for further guidance on suitability for given applications.

Manufacturing standard

Andover Washed block paving is manufactured using a semi-dry process and is compliant to European Standard BS EN 1338.

All Aggregate Industries' products are manufactured in accordance with ISO 9001 with factory compliance to ISO 14001.

Performance

Strength: The strength requirements are met to the manufacturing standard.

Slip and skid resistance: The potential for slip is 'low' in accordance to the manufacturing standard.

Complementary products

Complements Andover Textured block paving plus Malvern flag paving and Countryside Classic kerbs. Made to order Andover washed steps also available.



Colour swatches



1. Silver Grey
2. Anthracite Charcoal

Andover Washed block paving

Size (mm)	300x300	300x200	200x200	200x100	100x100	600x200
Thickness (mm)	80	80	80	80	80	80
Weight (kg)	16.5	10.9	7.3	3.6	1.7	21
Units/m ² (approx)	11.11	16.7	25	50	100	8.33
No. per pack	54	108	106	320	560	36
M ² /pack	4.86	6.46	6.40	6.40	5.60	4.32
Pack weight (T)	0.89	1.18	1.17	1.16	1.00	0.76
Colour available	*All Cols	*All Cols	*All Cols	*All Cols	*All Cols	*All Cols
Chamfered	No	No	No	No	No	No



Q24. For NBS clauses, refer to Charcon technical services

Andover Washed block paving comes banded and shrink-wrapped to a pallet. Available as an Infiltra concrete block permeable paver (CBPP) in 200x134x80 on MTO Basis. Coated with USP (Urban Surface Protection) to protect against everyday contaminants on MTO basis. Andover Washed complete step and tread unit available MTO in Silver Grey and Anthracite Charcoal.

Andover Washed block paving product information

Sustainability and local sourcing

Energy use: Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2012 based on a 2008 base line.

Recyclable: 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

Manufacturing location: produced in the UK, with locally sourced materials under strict environmental and social legislation, for local supply.

Responsible sourcing: Aggregate Industries is the first company in the world to achieve a BES 6001:2008 Responsible Sourcing Certificate from BRE Global. Products are assessed on:

- quality management
- environmental management
- health and safety management
- greenhouse gas emissions
- minimising raw material usage
- labour practice
- biodiversity
- community engagement.

Key aggregates and recycled content

Andover Washed is manufactured from specially selected granite aggregates with a minimum of 50% recycled material in the back mix. It is made in a semi-dry process and the face surface is then washed.

Generic green guide rating*

Concrete Block Pavers, CBP (80mm) over prepared recycled sub-base - **A rated.**

Concrete Block Pavers, CBP (80mm) over prepared sub-base - **B rated.**

Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.aggregate.com

Installation standard

Lay fine aggregate bedding course (to BS EN 12620 Gf85 0/4 mp) to a final compacted thickness of 50mm (in accordance with BS 7533: Part 3).

Maintenance and cleaning

Urban Surface Protection can be applied to this product at manufacturing stage on a made to order basis.

After laying light coloured paving on site, care should be taken to protect from dirt and detritus while the remaining construction works are completed.

Charcon can supply on request advice on specific stain removal and general maintenance, suitable cleaning products and referrals to specialist cleaning companies.

COSHH data

Full COSHH data on Charcon products is available on request. Please call the Technical helpline on 01335 372222.

Technical support

Detailed guidance and assistance with the preparation of specification of Charcon hard landscaping products, including model clauses, is available through the sales office. A free technical design service is also available.

For further information, please refer to Charcon technical services on 01335 372222.

*Ratings based upon generic green guide values (2009) supplied by BRE Global Ltd, www.thegreenguide.co.uk

Hulland Ward, Ashbourne,
Derbyshire DE6 3ET

Tel: 01335 372222

Fax: 01335 370074

www.charcon.com



A member of the Holcim Group